



Customer information packet

XM322562T

25//20HP, 1180//985RPM, 3PH, 60//50HZ, 324T

Class - CLI GP D; CLII GP F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	324T
Frame Material	Iron
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	CLI GP D; CLII GP F,G
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	25.000 HP @ 60 HZ 20.000 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 190.0 V @ 50 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ
Agency Approvals	UL CSA EEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	31.000 A @ 380.0 V 32.000 A @ 460.0 V 62.000 A @ 190.0 V 63.000 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT

Part detail

Revision	C
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	12WGY116
Layout	12LYL018
Eff. date	11-22-2024
CD Diagram	CD0180
Poles	06
Leads	9#8
Proprietary	False
Created date	03-19-2021

Efficiency @ 100% Load	93.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	31.0 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	NONE
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1500 rpm
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1260M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	32.00 IN
Power Factor	79
Product Family	General Purpose
Pulley Face Code	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	2.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1180 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2	None
-------------------	------

Nameplate

NP0887XPSLEV											
NO.						CC	010A				
S/N						TEMP CODE		T3C			
SPEC.	12-0000-2081					INV.TYPE		PWM			
CAT.NO.	XM322562T					C HP FR	60	C HP TO	90		
HP	25//20					CT HZ FROM	6	CT HZ TO	60		
VOLTS	230/460//190/380					VT HZ FROM	6	VT HZ TO	60		
AMPS	63/32//62/31				MAG CUR	28/14					
RPM	1180//985				MX RPM	1500					
HZ	60//50	PH	3	CL	B	NOM.EFF.	93				
SER.F.	1.00	DES	A	SL HZ	1	WK2	11.5				
FRAME	324T	RATING		40C AMB-CONT							
	NEMA MG-1 PART 5, IP54										
	1.15 SF ON SINE WAVE										

AC Induction Motor Performance Data

Record # 34364

Typical performance - not guaranteed values

Winding: 12WGY116-R003		Type: 1260M	Enclosure: XPFC		
Nameplate Data		460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)	25//20	Full Load Torque	111 LB-FT		
Volts	230/460//190/380	Start Configuration	direct on line		
Full Load Amps	63/32//62/31	Breakdown Torque	308 LB-FT		
R.P.M.	1180//985	Pull-up Torque	117 LB-FT		
Hz	60//50	Phase	3	Locked-rotor Torque	171 LB-FT
NEMA Design Code	A	KVA Code	H	Starting Current	198 A
Service Factor (S.F.)			1	No-load Current	13.8 A
NEMA Nom. Eff.	93	Power Factor	79	Line-line Res. @ 25°C	0.27033 Ω
Rating - Duty	40C AMB-CONT		Temp. Rise @ Rated Load		46°C
			Locked-rotor Power Factor		28
			Rotor inertia		11.5 LB-FT2

Load Characteristics 460 V, 60 Hz, 25 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	43	65	75	79	81	81
Efficiency	89.1	92.8	93.5	93.2	92.6	91.5
Speed	1195.4	1191.8	1188.2	1183.9	1179.3	1172.9
Line amperes	15.6	19.7	25.4	31.9	39.2	49.1


ABB Motors and Mechanical Inc.

WINDING # 12WGY116

Typical performance - not guaranteed values.

25 HP 3 PH 60 HZ 1183.9 RPM 460 V 1260M

TORQUES (LB-FT): PO=308 PU=117 LR=171 LRA=198



AC Induction Motor Performance Data

Record # 34365

Typical performance - not guaranteed values

Winding: 12WGY116-R003		Type: 1260M	Enclosure: XPFC	
Nameplate Data		380 V, 50 Hz: High Voltage Connection		
Rated Output (HP)	25//20	Full Load Torque	107 LB-FT	
Volts	230/460//190/380	Start Configuration	direct on line	
Full Load Amps	63/32//62/31	Breakdown Torque	298 LB-FT	
R.P.M.	1180//985	Pull-up Torque	123 LB-FT	
Hz	60//50	Phase	3	
NEMA Design Code	A	KVA Code	H	
Service Factor (S.F.)	1			
NEMA Nom. Eff.	93	Power Factor	79	
Rating - Duty	40C AMB-CONT			

Load Characteristics 380 V, 50 Hz, 20 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	43	65	75	79	81	81
Efficiency	86.4	91.2	92.2	92.3	91.6	90.3
Speed	996	992	989	984	980	974
Line amperes	15.4	19.3	24.8	31.1	38.2	47.9


ABB Motors and Mechanical Inc.


WINDING # 12WGY116

Typical performance - not guaranteed values.


20 HP 3 PH 50 HZ 984 RPM 380 V 1260M

TORQUES (LB-FT): PO=298 PU=123 LR=179 LRA=194





CD0180

LOW VOLTAGE
(2D)HIGH VOLTAGE
(1D)

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10:25:29 02/19/2019

BY: ENBRIRO

MTL: —



BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1

CD0180