



Customer information packet

ZDM3770T

7.5HP, 1770RPM, 3PH, 60HZ, 213TC, 0738M, TEBC

Class - None

Division - Not Applicable

Specifications

Enclosure	TEBC
Frame	213TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	BLOWER
Current @ Voltage	9.500 A @ 460.0 V 19.000 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	ENCODER
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	9.5 a
Insulation Class	H

Part detail

Revision	B
Type	AC
Mech. spec.	07D515
Base	
Status	PRD/A
Elec. spec.	07WGT510
Layout	07LYD515
Eff. date	09-30-2025
CD Diagram	CD0005
Poles	04
Leads	9#14
Proprietary	False
Created date	01-28-2021

Inverter Code	Inverter Duty
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	4000 rpm
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0738M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	25.58 IN
Power Factor	81
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	1.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1770 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4539L									
CAT.NO.	ZDM3770T								
SPEC.	07D515T510Z1								
FRAME	213TC			H.P.	7.5 TE				
VOLTS	230/460								
MAG. CUR.	8.6/4.3			F.L. AMPS				19/9.5	
R.P.M.	1770			R.P.M. MAX		4000			
HZ.	60		PH.	3	CLASS		H		
SER.F.	1.00		DES.	A	SL HZ		1		
NEMA NOM. EFF.	91.7		WK2	0.934					
BLWR V		PH		HZ		AMPS			
RATING	40C AMB-CONT								
DE	6307	ODE		6206					
CC	010A	SN							
	1000:1 CT/VT								

NP VOLTS	230/460	WYE CONN EQ CKT OHMS PER PHASE (BASE RATING, 20C)					
NP AMPS	19/9.5	Base Volt	460	R1	0.784	X1	2.650
HP	7.5	NL AMPS	4.07	R2	0.464	X2	2.040
BASE SPEED	1769	Slip (HZ)	1.03			XM	62.900
PHASE/HZ	3/60	WK ² (lb-ft ²)	0.934				

Rated Full Load Data

	RPM	HP	Torque	Volts	Freq-Hz	Amps
Base Speed	1769	7.5	22.3	460	60	9.4
Max Speed	2653	7.5	14.9	460	90	8.9
CT Min Speed	1,769	0.008	22.3	0.46	0.06	9.4

Load Performance at Base Speed

	RPM	HP	Torque	Volts	Freq-Hz	Amps
No Load	1799	0.0	0.0	460	60	4.1
1/4	1792	1.9	5.5	460	60	4.6
1/2	1785	3.7	11.0	460	60	5.8
3/4	1777	5.6	16.6	460	60	7.5
Full Load	1769	7.5	22.3	460	60	9.4
O/L	1734	15.0	45.4	460	60	18.7


Blower Data	Volts	Ph/Hz	FL Amps	L R Amps	Frame	CFM

Remarks: Calculated Data

DR BY USBRRANI		A-C MOTOR	07WGT510
CK BY CD		PERFORMANCE	
APP BY USBRRANI		CURVES	
DATE 3/21/2025			Record: 86626



NP VOLTS	230/460	WYE CONN EQ. CKT OHMS PER PHASE (BASE RATING, 20C)		
NP AMPS	19/9.5	R1	0.784	X1 2.650
HP	7.5	R2	0.464	X2 2.040
BASE SPEED	1769			XIM 62.900
PHASE/HZ	3/60			
		Base Volt	460	
		NL AMPS	4.07	
		Slip (Hz)	1.03	
		WK ² (lb-ft ²)	0.934	



Calculated Data
Data Valid For Nameplate Speed Range only

BALDOR • RELIANCE


DR BY USBRRANI
CK BY CD
APP BY USBRRANI
DATE 3/21/2025

**A-C MOTOR
PERFORMANCE
CURVES**

07WGT510
Record: 86626

NP VOLTS	230/460	0	0	WYE CONN. EQ. CKT. OHMS PER PHASE (BASE RATING, 20C)			
NP AMPS	19/9.5	Base Volt	460	R1	0.784	X1	2.650
HP	7.5	NL AMPS	4.07	R2	0.464	X2	2.040
BASE SPEED	1769	Slip (HZ)	1.03	XM			
PHASE/HZ	3/60	WK2 (lb-ft2)	0.934	62.900			

Vector PWM Inverter Duty
Variable Speed AC Motor Curves



Calculated Data
Data Valid For Nameplate Speed Range only

BALDOR • RELIANCE	DR BY <u>USBRANI</u>	A-C MOTOR	07WGT510
	CK BY <u>CD</u>	PERFORMANCE	
	APP BY <u>USBRANI</u>	CURVES	
	DATE <u>3/21/2025</u>		Record: 86626

