



Customer information packet

ZDWNM3611T

3HP, 1760RPM, 3PH, 60HZ, 184TC, 3640M, TENV, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	184TC
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.100 A @ 460.0 V 8.200 A @ 230.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	ENCODER
Front Face Code	Encoder/Feedback Device
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	4.1 a

Part detail

Revision	H
Type	AC
Mech. spec.	36J562
Base	
Status	PRD/A
Elec. spec.	36WGS952
Layout	36LYJ562
Eff. date	09-27-2024
CD Diagram	CD0005
Poles	04
Leads	9#16
Proprietary	False
Created date	07-03-2012

Insulation Class	H
Inverter Code	Inverter Duty
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	6000 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3640M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	19.27 IN
Power Factor	78
Product Family	Wash Down
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1760 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1609L									
CAT NO	ZDWNM3611T								
SPEC.	36J562S952Z1								
FRAME	184TC			HP	3 TE				
VOLTS	230/460								
MAG CUR	4.2/2.1			FLA	8.2/4.1				
RPM	1760		RPM MAX			6000			
HZ	60		PH	3		CLASS	H		
SER.F.	1.00		DES	B		SL HZ	1.4		
NEMA-NOM-EFF	89.5		WK2	0.372					
BLWR V			PH			HZ			A
RATING	40C AMB-CONT								
DE BRG	6206		ODE BRG			6205			
CC	010A		SER.NO						



AC Induction Motor Performance Data
 Record # 39007
 Typical performance - not guaranteed values

Winding: 36WGS952	Type: 3640M	Enclosure: TENV
--------------------------	--------------------	------------------------

Nameplate Data				General Characteristics at 460 V, 60 Hz: High Volt Connection			
Rated Output (HP)	3			Full Load Torque	9.1 LB-FT		
Volts	208-230/460			Start Configuration	DOL		
Full Load Amps	8.6-8.2/4.1			Break Down Torque	35 LB-FT		
R.P.M.	1760			Pull-Up Torque	18.8 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque	22.7 LB-FT		
NEMA Design Code	B	KVA Code	K	Starting Current	32.9 Amps		
Service Factor	1			No-load Current	2.09 Amps		
NEMA Nom. Eff.	89.5	P.F.	78	Line-line Res. @ 25°C.	3.3157 Ohms		
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	74°C		
S.F. Amps				Temp. Rise @ S.F. Load			


Load Characteristics at 460 Volts, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	38	60	71	78	82	84	
Efficiency	83.8	89.3	90.4	90.3	89.6	88.5	
Speed	1790.1	1780.3	1769.9	1758.7	1746.6	1732.6	
Line Amperes	2.29	2.72	3.34	4.05	4.86	5.75	


Baldor Electric Company Fort Smith, Arkansas



Catalog	ZDWNM3611T	NP VOLTS	230/460	ENCLOSURE	TENV	WYE CONN EQ CKT OHMS PER PHASE (BASE RATING, 20C)			
FRAME	184TC	NP AMPS	8.2/4.1	Base Volts	460	R1	1.640	X1	5.143
HP	3 HP	DUTY	Cont	Base AMPS	4.05	R2	1.260	X2	4.486
BASE SPEED	1800	MAX SAFE RPM	6000	Slip Hz	1.37	XM		120.167	
PHASE/HZ	3/60	AMB°C/INSUL.	40/H	WK ² (lb-ft ²)	0.372				



Remarks: Calculated Data



A MEMBER OF THE ABB GROUP

DR BY ENR

CK BY

APP BY ENR

DATE 3/6/2013

A-C MOTOR

PERFORMANCE CURVES

36J562S952Z1

ISSUE DATE 3/6/2013

